

Eco 150 TMP

Turns your tractor into a high output chipper

GreenMech
The Professionals' Choice



Customer category

Landscaper • Estate Maintenance • Contractor

Maximising the capability of your compact tractor fleet, without buying extra horsepower to chip waste brush and forestry trimmings has to be a very cost-effective manoeuvre. The ECO 150 TMP is a three-point linkage mounted machine, powered by the Power-take-off shaft of the compact tractor to drive the flywheel, while the tractor hydraulics are used to control the twin, hydraulically powered feed rolls - resulting in a very cost-effective investment. It has a 150mm x 150mm in-feed opening and can be driven by tractors with up to 45 pto hp. The Eco 150 TMP is typically used in landscape, golf course and large estates where compact tractors are employed to carry out a wide variety of duties.

The backbone of the Eco 150 TMP design is based on a deep beam, high tensile steel chassis which creates tremendous strength and ensures a robust performance. A new, generous in-feed hopper, measuring 800mm x 700mm, means that free-flow of bulky material can be handled without having to trim to a more manageable size. As the material passes through twin, hydraulically powered feed rollers, the patented, electronically controlled 'No-Stress' feed system will monitor the tractor's engine revs and will manage the feed rollers for maximum chipping efficiency.

Eco 150 TMP

Technical Specification...

Key features

- ⦿ 150mm chipping capacity
- ⦿ 25-45hp tractor requirement
- ⦿ Disc-Blade chipping technology
- ⦿ Spring-tensioned twin feed rollers
- ⦿ No-Stress power control
- ⦿ Off-set infeed loading
- ⦿ 490kg weight



Capacity	150mm
Engine Make	n/a
Engine	n/a
Fuel	n/a
Tractor Required	25 - 45hp
Chipping Flywheel	Disc Type
Flywheel Speed	2400rpm
Blades	2
Hydraulic Feed Rollers	Spring Tensioned Twin
Turntable	n/a
Power Control	No-Stress
Fuel Capacity (engine)	n/a
Tyre Size (towed)	n/a
Spare Wheel	n/a

Tonnes per hour	4.5
Infeed Chute Aperture	800mm x 700mm
Infeed Throat Size	150mm x 150mm
Discharge Chute	280° Rotation
Hydraulic Oil Capacity	n/a
Clutch	n/a
Hour Meter	Standard
Length (transport)	1060mm
Width (transport)	1745mm
Height	2220mm
Weight	490kg
Sound Power LWA	117dB(A)
Sound Pressure LPA	93dB(A)