

SURE-Trak 19-28

Key features

- SURE-Trak System (Patent Pending)
- 190mm chipping capacity
- 48hp Kubota diesel engine
- Disc-Blade chipping technology
- Twin hydraulic feed rollers
- No-Stress power control
- Patented SAFE-Trak system
- 2100kg weight
- Options include Winch, Emergency Recovery Kit, Lighting Tower and Tool Box



















For more challenging ground and even steeper slopes

Even more reason to be the ultimate tracked chipper for highways and railway cuttings

Based on the well-established SAFE-Trak, we have gone one better and incorporated the SURE-Trak System (Patent Pending) as a standard feature into our new model.

We know there are occasions when operators encounter either uncomfortable ground undulations - when the ground levels are significantly different between the two tracks - or need to safely climb slopes in excess of 35 degrees. The new SURE-Trak System ensures that both challenges can be safely met.

The SURE-Trak System is GreenMech's pivoting independent track assembly which further increases the 19-28's stability and broadens its operating profile over steep and uneven ground. The independently pivoting track assemblies allow each track to maintain contact with the ground while following the differing contours and so provide a surer footprint and improved stability.

Furthermore, the pivoting track system allows safer traversing and climbing of steeper slopes. Its assistance in maintaining the body of the machine level also protects the engine by keeping it within its approved manufacturer limits of tilt. This levelling is achieved by the operator making both side-to-side and longitudinal adjustments to the angle of the machine.

The SURE-Trak System therefore provides extra adjustment above normal tolerances and so ensures the safety of operator, crew and machine in challenging conditions.

SURE-Trak 19-28 comes with all the features and options already available on SAFE-Trak 19-28.













	Sure-Trak 19-28
Capacity	190mm
Engine Make	Kubota
Engine	48hp
Fuel	Diesel
Tractor Required	n/a
Chipping Flywheel	Disc Type
Flywheel Speed	1400rpm
Blades	4
Hydraulic Feed Rollers	Spring Tensioned Twin
Turntable	n/a
Power Control	No-Stress
Fuel Capacity (engine)	60 L
Tyre Size (towed)	n/a
Spare Wheel	n/a
Tonnes per hour	7
Infeed Chute Aperture	1200mm x 840mm
Infeed Throat Size	190mm x 280mm
Discharge Chute	280° Rotation
Hydraulic Oil Capacity	50 L
Clutch	n/a
Hour Meter	Standard
Length (transport)	3346mm
Width (transport)	1450mm
Height	2571mm
Weight	2100kg
Sound Power LWA	120dB(A)
Sound Pressure LPA	96dB(A)
Paint Colour	Standard Green or options







Your authorised GreenMech dealer is:



