

Safe-Trak 19-28

Goes where men fear to tread

GreenMech
The Professionals' Choice



Customer category

Contractors • Powerline, Rail and Highway clearance

Building on proven technology, the Safe-Trak 19-28 is a higher capacity and heavy-duty version of the Safe-Trak 16-23, of the provides unrivalled stability on such applications as railway embankments and cuttings. A massive 550mm ground clearance means that large obstacles such as tree-stumps can be straddled and, each track can be independently adjusted to provide safe travel across slopes of up to 35 degrees. The main advantage of having such flexibility is to take the machine to the maintenance point instead of having to bring material out by hand – a major time/cost benefit. This unit is powered by a 48hp Kubota diesel engine and has bags of power to take the largest of wood profile.

The backbone of the Safe-Trak 19-28 design is based on a deep beam, high tensile steel chassis which creates tremendous strength and ensures a robust performance. A new, generous in-feed hopper, measuring 1200mm x 840mm, means that free-flow of bulky material can be handled without having to trim to a more manageable size. As the material passes through aggressive 190mm x 280mm twin, hydraulically powered feed rollers, the patented electronically controlled No-Stress system automatically manages the throughput of material to maximise chipping efficiency.

Safe-Trak 19-28

Technical Specification...

Key features

- ⊙ 190mm chipping capacity
- ⊙ 48hp Kubota diesel engine
- ⊙ Disc-Blade chipping technology
- ⊙ Twin hydraulic feed rollers
- ⊙ No-Stress power control
- ⊙ Patented SAFE-Trak system
- ⊙ Bottom-bar safety mechanism
- ⊙ 2000kg weight



Capacity	190mm
Engine Make	Kubota
Engine	48hp
Fuel	Diesel
Tractor Required	n/a
Chipping Flywheel	Disc Type
Flywheel Speed	1400rpm
Blades	4
Hydraulic Feed Rollers	Spring Tensioned Twin
Turntable	n/a
Power Control	No-Stress
Fuel Capacity (engine)	60 L
Tyre Size (towed)	n/a
Spare Wheel	n/a

Tonnes per hour	7
Infeed Chute Aperture	1200mm x 840mm
Infeed Throat Size	190mm x 280mm
Discharge Chute	280° Rotation
Hydraulic Oil Capacity	50 L
Clutch	n/a
Hour Meter	Standard
Length (transport)	3346mm
Width (transport)	1450mm
Height	2571mm
Weight	2000kg
Sound Power LWA	120dB(A)
Sound Pressure LPA	96dB(A)